

Show different UI texts depending on the template used

It is possible to show different UI text depending on the template requested by the application - either the template specified in the Agent's template field or for mobile connect.

Step-by-step guide Example 1

The same application could show very different template and user interface text, depending on the template name listed in the Template Names field of Ubilogin Management. By default, the first template name listed will be used.

1. Modify messages.properties

```
# Christmas messages
christmas = christmas.properties
errors/christmas = christmas_errors.properties
christmas_sv = christmas_sv.properties
errors/christmas_sv = christmas_errors_sv.properties

# internal messages
internal = internal.properties
errors/internal = internal_errors.properties
internal_sv = internal_sv.properties
errors/internal_sv = internal_errors_sv.properties

# external messages
external = external.properties
errors/external = external_errors.properties
external_sv = external_sv.properties
errors/external_sv = external_errors_sv.properties
```

2. Modify custom/messages/christmas.properties to contain text in default language

```
HEADER_TEXT1 = Merry Christmas!
HEADER_TEXT2 = Have a happy and prosperous new year!
PASSWORD_INTRO_TITLE = Ho Ho Ho!
```

3. Modify custom/messages/christmas_sv.properties to contain text in Swedish language

```
HEADER_TEXT1 = God Jul!
HEADER_TEXT2 = Gott nytt år!
PASSWORD_INTRO_TITLE = Ho Ho Ho!
```

4. Modify custom/messages/christmas_errors.properties to contain error text in default language

```
USER_NOT_FOUND = Santa cannot find you on his list. Have you been naughty?
ACCOUNT_EXPIRED = Are you too old for this?
```

5. Modify custom/messages/christmas_errors_sv.properties to contain error text in Swedish language

```
USER_NOT_FOUND = Santa kan inte hitta dig på sin lista. Har du varit stygg?
ACCOUNT_EXPIRED = Är du för gammal för detta?
```

6. An integrated application can set the template dynamically using the appropriate API. For Ubisecure SAML SP for Java, the template is set in the AuthnRequestEvent using the setTemplate method.

```
@Override
public void authnRequest(AuthnRequestEvent e) {
    e.getAuthnRequest().setTemplate("christmas");
}
```



The name of the template chosen currently is visible at the /uas/info page if enabled.

The name of the template chosen currently is visible in the view() array in the source code of the login or error screens generated by Ubisecure SSO.

Related articles

- [Select different authentication methods using the acr_values parameter](#)
- [Admin/self-service UI \[Warning: Property for 'xx.xx.xx.xx' not found\]](#)
- [Show different UI text using the oidc display parameter](#)
- [Show different UI texts depending on the template used](#)
- [Show different help text depending on the application used](#)