

Show different UI text using the oidc display parameter

It is possible to show different UI text depending on the template requested by the application by requesting a different display value in the OIDC authentication request.

Step-by-step guide

For an application using OpenID Connect.

The same application could show very different template and user interface text, depending on a combination of the template name listed in the Template Names field of UbiLogin Management and the value of the "display" variable sent in the authentication request.

The corresponding template will be chosen via the oidc.display value ("page", "template", "touch" or "wap").

Modify templates.properties

1. Modify custom/templates.index to contain text the various templates

```
christmas = templates/christmas.properties
summer = templates/summer.properties
```

2. Modify custom/templates/christmas.properties to contain settings for Christmas template


```
oidc.display = page
@LOGIN_TITLE_COLOR@ = red
```

3. Modify custom/templates/summer.properties to contain settings for summer template

```
oidc.display = touch
@LOGIN_TITLE_COLOR@ = blue
```

4. Set both template names in the "Template Names" field of the agent
5. When creating an authentication request, specify the corresponding value in the display query string attribute. The following example will activate the "summer" template and correspondingly any user interface text specified with that template name will be used.

```
GET https://sso.example.com/uas/oauth2/authorization?
response_type=code&scope=openid&client_id=2001221477&redirect_uri=https://client.example.com
/response&state=40e1bfc0-4587-4859-be08-a58e3fffa37a&display=touch
```

 The name of the template chosen currently is visible at the /uas/info page if enabled.

The name of the template chosen currently is visible in the view() array in the source code of the login or error screens generated by UbiSecure SSO.

Related articles

- [Select different authentication methods using the acr_values parameter](#)
- [Admin/self-service UI \[Warning: Property for 'xx.xx.xx.xx' not found\]](#)
- [Show different UI text using the oidc display parameter](#)
- [Show different UI texts depending on the template used](#)
- [Show different help text depending on the application used](#)