

Settings related to Ubisecure SSO - CustomerID

master.secret

The value of `master.secret` is used to encrypt the contents of Ubisecure Directory. This seed secret value must match the value used by the Ubisecure SSO for `master.secret`. This value is found in the Ubisecure SSO configuration file `ubisecure/ubilogin-ss0/ubilogin/SYS.config`, where `SYS` can be `unix` or `win32` depending on the platform where the server is running on. Usually this property is included in the `eidm2_generated.properties` file and there is no reason to modify it or reset it.

Default is `master.secret`. However do not use this default setting. Always set your own or use the generated value.
Example:

```
master.secret = vC4DRX_Bjtyon867uoZ%0&I.
```

sso.template

This property defines the name of the user interface template that is used in the Ubisecure SSO. The template will be set up in the REST initialization call when the `initializeRepository` parameter has been set.

Default is `default federation`.
Example:

```
sso.template = customer
```

uas.url

This property is needed if the user is to be automatically transferred to an application after a successful registration. It should define the address of Ubisecure SSO. E.g. `https://sso.example.com/uas`). Usually this property is included in the `eidm2_generated.properties` file and there is no reason to modify it or reset it.

Default is `https://localhost:8443/uas`.
Example:

```
uas.url = https://localhost:8443/uas
```